



// UNDERGROUND CABLE PULLER

HYDRA 985 PULLER "HYDRA HOG"



// UNIT SPECIFICATIONS

MAX LINE PULL: 24,000 LBS

MANDREL RACKS: HYDRAULICALLY CONTROLLED W/ LOAD LOCK CYLINDERS

ENGINE SPECS: DIESEL YANMAR 3TNV88C-DYEM 3 CYLINDER | 36.8 HP @ 3,000 RPM WITH BLOCK HEATER

AXLE: 20,000 LB. STUB AXLES WITH MACHINED ATTACHMENT PLATES

REEL SHAFT: 2 1/2" HEAT TREATED REEL SHAFT WITH CENTERING CONES, LOCKING COLLARS AND BEARINGS

REEL CAPACITY: 50" UP TO 108" D | MAX WIDTH OF 56"



// POWER UNIT

- ELECTRIC THROTTLE ACTIVATION/FRONT & REAR
- CLOSED LOOP HYDRAULIC SYSTEM
- TWO SPEED FINAL DRIVE W/ ELECTRIC ACTIVATED SHIF
- LOAD LOCK CYLINDER PROVIDES DRIVE ROLLER PRESSURE TO REEL
- 2 7/16" CHROME PLATED DRIVE SHAFT
- AUXILARY POWER SHAFT WITH BAYONET
- TACHOMETER, HOUR METER, TEMP/VOLT GAUGES
- FULL FLOW FILTRATION WITH RELIEF AND CONDITION INDICATOR
- FULLY HOODED WITH HINGED DOORS FOR ACCESS TO ENGINE

// ADDITIONAL SPECIFICATIONS

- HIGH VISIBILITY STROBES
- INCLUDES TONGS
- POSITIVE FRICTION DRIVE SYSTEM
- REAR CONTROLS

