



HYDRA 985 PULLER

CABLE TRAILER



SCAN TO LEARN MORE ABOUT THIS TRAILER

UNIT SPECIFICATIONS

- MAX LINE PULL: 24,000 LBS
- MANDREL RACKS: HYDRAULICALLY CONTROLLED W/ LOAD LOCK CYLINDERS
- ENGINE SPECS: DIESEL YANMAR 3TNV88C-DYEM 3 CYLINDER, 36.8 HP @ 3,000 RPM WITH BLOCK HEATER
- AXLE: 20,000 LBS STUB AXLE WITH MACHINED ATTACHMENT PLATES
- REEL SHAFT: 2 1/2" HEAT TREATED REEL SHAFT WITH CENTERING CONES, LOCKING COLLARS AND BEARINGS
- REEL CAPACITY: 50" UP TO 108" D | MAX WIDTH OF 56"
- HIGH VISIBILITY STROBES
- POSITIVE FRICTION DRIVE SYSTEM
- REAR CONTROLS

OPTIONAL

- BREAKAWAY REAL-SIZE

MODEL	DIAMETER	WIDTH
6036	60"	36"
8050	80"	50"
6036	60"	36"
8050	80"	50"

POWER UNIT

- ELECTRIC THROTTLE ACTIVATION/FRONT & REAR
- TWO SPEED FINAL DRIVE W/ ELECTRIC ACTIVATED SHIF
- LOAD LOCK CYLINDER PROVIDES DRIVE ROLLER PRESSURE TO REEL
- AUXILARY POWER SHAFT WITH BAYONET
- TACHOMETER, HOUR METER, TEMP/VOLT GAUGES
- FULL FLOW FILTRATION WITH RELIEF AND CONDITION INDICATOR

- PULLING REAL-SIZE

MODEL	DIAMETER	FLANGE WIDTH	CORE DIAMETER
663036	66"	30"	36"
723036	72"	30"	36"