

REELSTRONG CLD20

CABLE TRAILER



**SCAN TO LEARN MORE
ABOUT THIS TRAILER**

LOAD CAP. (LBS)	GVWR (LBS)	TRAILER	MAX REEL DIMENSION	REEL BAR DIA.	ENGINE
20,000	27,600	8.5' W x 16' 7" L	120" Dia. x 62" W	3" (Pinless)	13 HP 10.4 GPM @ 1300 PSI

TRAILER EQUIPPED WITH:

- PINLESS REEL BAR SECUREMENT
- 15 GAL. RESERVOIR TANK
- POWER PAY-OUT AND REWIND
- 16" BRONZE VENTILATED TENSION BRAKES
- 12,000 LBS STATIC FRONT JACK
- ELECTRIC BRAKES
- GROUNDING LUG
- 6-POSITION ADJUSTABLE HITCH
- PINLESS QUICK DEPLOY OUTRIGGERS
- WHEEL CHOCKS
- (6) D-RINGS

EQUIPMENT SPECIFICATIONS

- GALVANIZED
- TRI-AXLE, SINGLE WHEELS
- 3,300 LBS TORQUE TAKE-UP RETRIEVER
- KNUCKLED-DOWN LIFT ARMS FOR INDUSTRY'S LOWEST COG
- 4,200 LBS PULLING CAPACITY FROM CENTER OF REEL