



**SCAN TO LEARN MORE ABOUT
OUR TRAILER OFFERINGS**

PAYLOAD (LBS)	GVWR (LBS)	OVERALL LENGTH (FT)	CURB WEIGHT (LBS)	DECK HEIGHT (IN)
40,000	47,850	31' 4" with 6' tail	8,380	34"

TRAILER EQUIPPED WITH:

FRAME	- MAINRAILS: W14" X 22 LBS. WIDE FLANGE I-BEAM, ONE PIECE COLD FORMED - HI-TENSILE 50,000 P.S.I. STEEL MAINRAILS FROM FRONT TO DRAWBAR TO REAR OF TRAILER - 8° BEAVER TAIL (SAFE LOW LOADING ANGLE)
CROSSMEMBERS	- 6" X 3.7 LBS. PER FT. I-BEAM PIERCED THROUGH MAINBEAM
DECKING	- NOMINAL 2" HARDWOOD
HEADBOARD	- 8" HIGH, FULL WIDTH OF TRAILER DRAWBAR STORAGE AREA
LIGHTS	- SEALED L.E.D., 12 VOLT, DOT APPROVED
WIRING HARNESS	- USA STAR PLUS SEALED MODULAR WIRING HARNESS W/ 7-WAY ATA PLUG
HITCH	- ONE PIECE SOLID CAST STEEL (ADJUSTABLE) LUNETTE EYE & FLANGE MOUNT
SAFETY CHAINS	- TWO 1/2" BLUE-KROME PLATED HIGH TEST, SAFETY HOOK W/ LATCH
PARKING JACK	- 70,000 LBS. STATIC / 40,000 LBS. LIFT (HEAVY DUTY 2-SPEED SCREW TYPE)
TIE DOWN	- FIVE PER SIDE - PATENTED "ROTO RINGS"® SWIVEL 360°
COLOR	- BLACK
TIRES	- EIGHT (8) 215/75R 17.5 (H) STEEL BELTED RADIAL
HUBS/WHEELS	- FOUR DISC TYPE HUBS, EIGHT 6.75 X 17.5, 8-BOLT, HUB-PILOTED DISC WHEELS
SUSPENSION	- HUTCH H-9700, THREE LEAF, CAPACITY 50,000 LBS. TANDEM
AXLES	- TWO 5" DIAMETER 22,500 LBS. EACH, H.M. SERIES BEARINGS (MAXIMUM AXLE TRACK WIDTH)
ALL WHEEL ABS	- TWO (2) 22.5K ANTI-LOCK BRAKE SYSTEM 4S2M SENSOR ALL WHEELS TWO MODULAR VALVES AIR BRAKES
PARKING BRAKE	- SPRING BRAKE ON ALL AXLES